

Fire Resistant Mat

PRODUCT PERFORMANCE

COMFORT	✓✓✓
GRIP	✓✓✓✓✓
WEAR	✓✓✓✓

CODE	SIZE
FR35	900 x 1500mm

24mm Thickness

NON FIRE RESISTANT MAT SAMPLE



Subjected to flame for 40 seconds.



Sample position soon after the burner is removed.



Mat burns with bright flame & fire propagation visible with heavy smoke.


FIRE RESISTANT MAT SAMPLE



Subjected to flame for 40 seconds.



Sample position soon after the burner is removed.



Sample does not propagate fire, slight smoke only.

FEATURES

- Ideal for fire hazardous areas, as the mat is inherent with a combination of properties for resisting fire.
- Does not emit chlorine or chlorinated gaseous compounds, such as hydrochloric acid fumes, sulfur mono-chloride and chlorine etc.
- Very low smoke emission.
- Excellent resistance to general weathering conditions and has inherent ageing resistance.
- Very good load bearing characteristics.
- Good wear and tear properties coupled with strength for more durability.
- Tested according to EN 13501-1 by Vienna, Austria and has classification Cfl-SI.
- Recommended for use in public places.

matTEK[®]
By Kenware Commercial

11 Pullman Place,
Emu Plains, NSW 2750 Australia
Phone 02 4720 4000
Fax 02 4720 4001
sales@mattek.com.au